





SPECIFICATION



RATING:	6A 125VAC, 4A 250VAC (UL, CUL)
	4(1)A 250V~ T85 (ENEC)
INSULATION RESISTANCE:	DC 500V 100MΩ OR MORE
CONTACT RESISTANCE:	DC 2-4V 1A 20mΩ OR LESS
WITHSTAND VOLTAGE:	AC 1500V FOR 1 Min
AMBIENT TEMPERATURE:	0~85°C
ELECTRICAL LIFE:	10,000 CYCLES

SIZE



W	PANEL THICK
19.2	0.75 ~ 1.25
19.4	1.25 ~ 2.00
19.8	2.00 ~ 3.00
MOUNTING HOLE (FOR REFERENCE)	

HOW TO ORDER

3022 — ☐ — ☐ — ☐ — ☐ — ☐ — ☐ — ☐ — ☐ — ☐

KNOB

NONE

K2:

K3:

PRINT

P0: NONE

P1:

P2:

P3:

P4:

P5:

P6:

P8:

LIGHT

L0: NONE

L2: AC250V
YELLOW NEON LAMP

L3: DC48V
RED LED

L4: AC250V
GREEN NEON LAMP

L5: AC125V
YELLOW NEON LAMP

L6: AC125V
GREEN NEON LAMP

L7: AC250V
6mm GREEN NEON LAMP

L8: 1/2 2.2KΩ
BLUE LED

CONTACT

C1: Ag ALLOY

TERMINAL

T2:4.75x0.8

T2A:1.8x0.8

CIRCUIT

S: SPST

D: DPST

KNOB COLOR

BK: BLACK

BU: BLUE

GN: GREEN

RD: RED

BODY COLOR

BK: BLACK

SW: SNOW WHITE