





SPECIFICATION



RATING:	10A 125VAC, 5A 250VAC (UL, CUL, ENEC)
INSULATION RESISTANCE:	DC 500V 100MΩ OR MORE
CONTACT RESISTANCE:	DC 2-4V 1A 20mΩ OR LESS
WITHSTAND VOLTAGE:	AC 1500V FOR 1 Min
AMBIENT TEMPERATURE:	0~85°C
ELECTRICAL LIFE:	10,000 CYCLES

SIZE



PC MOUNTING
(FOR REFERENCE)

HOW TO ORDER

3331 - □ - □ - □ - □ - □ - □

KNOB

K1:

K2:

K3:

RATING

P1: 230V 115V	P7: 15V 105V
P2: 240V 120V	P8: 120V 100V
P3: 220V 115V	P9: 24V 230V
P4: 240V 220V	P10: 230V 120V
P5: 220V 110V	P11: 115V 230V
P6: 230V 115V	

BRACKET

B1:

B2: 2-ø3.3

B4:

B5: 2-M3.0x0.5

TERMINAL

T1:

T2:

T3:

T4:

CIRCUIT

DD: DPDT

DS: DPST

SD: SPDT

SS: SPST

KNOB COLOR

BK: BLACK

RD: RED