

SPECIFICATION



CONTACT RATING	: 3A @120 VAC or 28 VDC (Q Contact)
ELECTRICAL LIFE:	: 30,000 make-and-break cycles at full load
CONTACT RESISTANCE	: 20 mΩ max. initial @2-4 VDC, 100 mA
INSULATION RESISTANCE	: 1,000 MΩ min.
DIELECTRIC STRENGTH	: 1,500 V RMS @ sea level.
OPERATING TEMPERATURE	: -30°C to +85°C

MATERIALS

- CASE - diallyl phthalate (DAP)
- TOGGLE HANDLE - Copper alloy , chrome plated
- BUSHING - Copper alloy , nickel plated
- HOUSING - Stainless Steel
- CONTACT AND TERMINAL - Copper alloy , silver plated
- SWITCH SUPPORT - Copper alloy , tin-plated



How do you build the switches you need!!

The TS-4 / TS-5 , please see the (A) ;

The TS-6/TS-7/TS-8/TS-9, please see the (B)

(A) TS - 4 - S E B Q - E - A5 - T3 - 2 -

Switch Function	Actuator	Bushing	Termination	Vertical support Bracket	Cap color																																																																																																																										
<table border="1" style="width: 100%;"> <tr><td>TS-4</td><td>SP on-none-on</td></tr> <tr><td>TS-4B</td><td>SP on-none-(on)</td></tr> <tr><td>TS-4A</td><td>SP on-off-on</td></tr> <tr><td>TS-4H</td><td>SP (on)-off-(on)</td></tr> <tr><td>TS-4I</td><td>SP on-off-(on)</td></tr> <tr><td>TS-5</td><td>DP on-none-on</td></tr> <tr><td>TS-5B</td><td>DP on-none-(on)</td></tr> <tr><td>TS-5A</td><td>DP on-off-on</td></tr> <tr><td>TS-5H</td><td>DP (on)-off-(on)</td></tr> <tr><td>TS-5I</td><td>DP on-off-(on)</td></tr> </table>	TS-4	SP on-none-on	TS-4B	SP on-none-(on)	TS-4A	SP on-off-on	TS-4H	SP (on)-off-(on)	TS-4I	SP on-off-(on)	TS-5	DP on-none-on	TS-5B	DP on-none-(on)	TS-5A	DP on-off-on	TS-5H	DP (on)-off-(on)	TS-5I	DP on-off-(on)	<table border="1" style="width: 100%;"> <tr><td colspan="2">For Bushing E/E1/F/F1</td></tr> <tr><td>S</td><td>9.40</td></tr> <tr><td>T</td><td>5.33</td></tr> <tr><td>U</td><td>7.37</td></tr> <tr><td colspan="2">For Bushing G/G1/J/J1</td></tr> <tr><td>V</td><td>10.41</td></tr> <tr><td>X</td><td>5.59</td></tr> <tr><td colspan="2">Locking Lever</td></tr> <tr><td>LK</td><td>Round top</td></tr> <tr><td>LK1</td><td>Flat top</td></tr> </table>	For Bushing E/E1/F/F1		S	9.40	T	5.33	U	7.37	For Bushing G/G1/J/J1		V	10.41	X	5.59	Locking Lever		LK	Round top	LK1	Flat top	<table border="1" style="width: 100%;"> <tr><td colspan="2">The 10-48 uns thread</td></tr> <tr><td>E (std.) flat</td><td>5.59</td></tr> <tr><td>F key-way</td><td>5.59</td></tr> <tr><td colspan="2">Non-thread</td></tr> <tr><td>E1 flat</td><td>5.59</td></tr> <tr><td>F1 key-way</td><td>5.59</td></tr> <tr><td colspan="2">1/4-40 uns thread</td></tr> <tr><td>G flat</td><td>7.87</td></tr> <tr><td>J key-way</td><td>6.60</td></tr> <tr><td colspan="2">Non-thread</td></tr> <tr><td>G1 flat</td><td>7.87</td></tr> <tr><td>J1 key-way</td><td>6.60</td></tr> <tr><td colspan="2">None</td></tr> <tr><td colspan="2">The actuator LK/LK1 No requirement to choose the bushing, unless the non-thd LKN / LK1N</td></tr> </table>	The 10-48 uns thread		E (std.) flat	5.59	F key-way	5.59	Non-thread		E1 flat	5.59	F1 key-way	5.59	1/4-40 uns thread		G flat	7.87	J key-way	6.60	Non-thread		G1 flat	7.87	J1 key-way	6.60	None		The actuator LK/LK1 No requirement to choose the bushing, unless the non-thd LKN / LK1N		<table border="1" style="width: 100%;"> <tr><td>B</td><td>solder lug</td></tr> <tr><td>C</td><td>P.C</td></tr> <tr><td>D</td><td>wire wrap</td></tr> <tr><td colspan="2">Contact Material</td></tr> <tr><td>Q</td><td>silver plated</td></tr> <tr><td>R</td><td>gold plated</td></tr> <tr><td>G</td><td>gold over silver</td></tr> <tr><td>K</td><td>tin plated</td></tr> <tr><td colspan="2">Epoxy seal</td></tr> <tr><td>(none)</td><td>none seal</td></tr> <tr><td>E</td><td>epoxy seal</td></tr> </table>	B	solder lug	C	P.C	D	wire wrap	Contact Material		Q	silver plated	R	gold plated	G	gold over silver	K	tin plated	Epoxy seal		(none)	none seal	E	epoxy seal	<table border="1" style="width: 100%;"> <tr><td>(none)</td><td>Vertical bracket</td></tr> <tr><td>A5</td><td>Vertical bracket</td></tr> <tr><td>A5S</td><td>Vertical bracket (snap-in)</td></tr> <tr><td colspan="2">Actuator Cap/ Rubber hood Sealing</td></tr> <tr><td colspan="2">Actuator Cap</td></tr> <tr><td>T3</td><td>9.40 (for actuator S/V/X)</td></tr> <tr><td colspan="2">Rubber Hood</td></tr> <tr><td>E1</td><td>for bushing G/J</td></tr> <tr><td>E7</td><td>for bushing E/F</td></tr> </table>	(none)	Vertical bracket	A5	Vertical bracket	A5S	Vertical bracket (snap-in)	Actuator Cap/ Rubber hood Sealing		Actuator Cap		T3	9.40 (for actuator S/V/X)	Rubber Hood		E1	for bushing G/J	E7	for bushing E/F	<table border="1" style="width: 100%;"> <tr><td>1</td><td>white</td></tr> <tr><td>2</td><td>black</td></tr> <tr><td>3</td><td>red</td></tr> <tr><td>4</td><td>yellow</td></tr> <tr><td>5</td><td>blue</td></tr> <tr><td colspan="2">RoHS code</td></tr> <tr><td colspan="2">H = RoHS Compliant</td></tr> </table>	1	white	2	black	3	red	4	yellow	5	blue	RoHS code		H = RoHS Compliant	
TS-4	SP on-none-on																																																																																																																														
TS-4B	SP on-none-(on)																																																																																																																														
TS-4A	SP on-off-on																																																																																																																														
TS-4H	SP (on)-off-(on)																																																																																																																														
TS-4I	SP on-off-(on)																																																																																																																														
TS-5	DP on-none-on																																																																																																																														
TS-5B	DP on-none-(on)																																																																																																																														
TS-5A	DP on-off-on																																																																																																																														
TS-5H	DP (on)-off-(on)																																																																																																																														
TS-5I	DP on-off-(on)																																																																																																																														
For Bushing E/E1/F/F1																																																																																																																															
S	9.40																																																																																																																														
T	5.33																																																																																																																														
U	7.37																																																																																																																														
For Bushing G/G1/J/J1																																																																																																																															
V	10.41																																																																																																																														
X	5.59																																																																																																																														
Locking Lever																																																																																																																															
LK	Round top																																																																																																																														
LK1	Flat top																																																																																																																														
The 10-48 uns thread																																																																																																																															
E (std.) flat	5.59																																																																																																																														
F key-way	5.59																																																																																																																														
Non-thread																																																																																																																															
E1 flat	5.59																																																																																																																														
F1 key-way	5.59																																																																																																																														
1/4-40 uns thread																																																																																																																															
G flat	7.87																																																																																																																														
J key-way	6.60																																																																																																																														
Non-thread																																																																																																																															
G1 flat	7.87																																																																																																																														
J1 key-way	6.60																																																																																																																														
None																																																																																																																															
The actuator LK/LK1 No requirement to choose the bushing, unless the non-thd LKN / LK1N																																																																																																																															
B	solder lug																																																																																																																														
C	P.C																																																																																																																														
D	wire wrap																																																																																																																														
Contact Material																																																																																																																															
Q	silver plated																																																																																																																														
R	gold plated																																																																																																																														
G	gold over silver																																																																																																																														
K	tin plated																																																																																																																														
Epoxy seal																																																																																																																															
(none)	none seal																																																																																																																														
E	epoxy seal																																																																																																																														
(none)	Vertical bracket																																																																																																																														
A5	Vertical bracket																																																																																																																														
A5S	Vertical bracket (snap-in)																																																																																																																														
Actuator Cap/ Rubber hood Sealing																																																																																																																															
Actuator Cap																																																																																																																															
T3	9.40 (for actuator S/V/X)																																																																																																																														
Rubber Hood																																																																																																																															
E1	for bushing G/J																																																																																																																														
E7	for bushing E/F																																																																																																																														
1	white																																																																																																																														
2	black																																																																																																																														
3	red																																																																																																																														
4	yellow																																																																																																																														
5	blue																																																																																																																														
RoHS code																																																																																																																															
H = RoHS Compliant																																																																																																																															

(B) TS - 6 - T E1 Q - E - S - T3 - 5 -

Horizon Right Angle	Vertical Right Angle	Switches Function	Actuator	Bushing	Contact Material	Actuator Cap																																																																																																																						
<table border="1" style="width: 100%;"> <tr><td>TS-6</td></tr> <tr><td>TS-6B</td></tr> <tr><td>TS-6A</td></tr> <tr><td>TS-6H</td></tr> <tr><td>TS-6I</td></tr> <tr><td>TS-7</td></tr> <tr><td>TS-7B</td></tr> <tr><td>TS-7A</td></tr> <tr><td>TS-7H</td></tr> <tr><td>TS-7I</td></tr> </table>	TS-6	TS-6B	TS-6A	TS-6H	TS-6I	TS-7	TS-7B	TS-7A	TS-7H	TS-7I	<table border="1" style="width: 100%;"> <tr><td>TS-8</td></tr> <tr><td>TS-8B</td></tr> <tr><td>TS-8A</td></tr> <tr><td>TS-8H</td></tr> <tr><td>TS-8I</td></tr> <tr><td>TS-9</td></tr> <tr><td>TS-9B</td></tr> <tr><td>TS-9A</td></tr> <tr><td>TS-9H</td></tr> <tr><td>TS-9I</td></tr> <tr><td>TS-82</td></tr> <tr><td>TS-82B</td></tr> <tr><td>TS-82A</td></tr> <tr><td>TS-82H</td></tr> <tr><td>TS-82I</td></tr> </table>	TS-8	TS-8B	TS-8A	TS-8H	TS-8I	TS-9	TS-9B	TS-9A	TS-9H	TS-9I	TS-82	TS-82B	TS-82A	TS-82H	TS-82I	<table border="1" style="width: 100%;"> <tr><td>SP on-none-on</td></tr> <tr><td>SP on-none-(on)</td></tr> <tr><td>SP on-off-on</td></tr> <tr><td>SP (on)-off-(on)</td></tr> <tr><td>SP on-off-(on)</td></tr> <tr><td>DP on-none-on</td></tr> <tr><td>DP on-none-(on)</td></tr> <tr><td>DP on-off-on</td></tr> <tr><td>DP (on)-off-(on)</td></tr> <tr><td>DP on-off-(on)</td></tr> <tr><td>SP on-none-on</td></tr> <tr><td>SP on-none-(on)</td></tr> <tr><td>SP on-off-on</td></tr> <tr><td>SP (on)-off-(on)</td></tr> <tr><td>SP on-off-(on)</td></tr> </table>	SP on-none-on	SP on-none-(on)	SP on-off-on	SP (on)-off-(on)	SP on-off-(on)	DP on-none-on	DP on-none-(on)	DP on-off-on	DP (on)-off-(on)	DP on-off-(on)	SP on-none-on	SP on-none-(on)	SP on-off-on	SP (on)-off-(on)	SP on-off-(on)	<table border="1" style="width: 100%;"> <tr><td colspan="2">For Bushing E/E1/F/F1</td></tr> <tr><td>S</td><td>9.40</td></tr> <tr><td>T</td><td>5.33</td></tr> <tr><td>U</td><td>7.37</td></tr> <tr><td colspan="2">For Bushing G/G1/J/J1</td></tr> <tr><td>V</td><td>10.41</td></tr> <tr><td>X</td><td>5.59</td></tr> </table>	For Bushing E/E1/F/F1		S	9.40	T	5.33	U	7.37	For Bushing G/G1/J/J1		V	10.41	X	5.59	<table border="1" style="width: 100%;"> <tr><td colspan="2">The 10-48 uns thread</td></tr> <tr><td>E flat</td><td>5.59</td></tr> <tr><td>F key-way</td><td>5.59</td></tr> <tr><td colspan="2">Non-thread</td></tr> <tr><td>E1 (std.) flat</td><td>5.59</td></tr> <tr><td>F1 key-way</td><td>5.59</td></tr> <tr><td colspan="2">1/4-40 uns thread</td></tr> <tr><td>G flat</td><td>7.87</td></tr> <tr><td>J key-way</td><td>6.60</td></tr> <tr><td colspan="2">Non-thread</td></tr> <tr><td>G1 flat</td><td>7.87</td></tr> <tr><td>J1 key-way</td><td>6.60</td></tr> </table>	The 10-48 uns thread		E flat	5.59	F key-way	5.59	Non-thread		E1 (std.) flat	5.59	F1 key-way	5.59	1/4-40 uns thread		G flat	7.87	J key-way	6.60	Non-thread		G1 flat	7.87	J1 key-way	6.60	<table border="1" style="width: 100%;"> <tr><td>Q</td><td>silver plated</td></tr> <tr><td>R</td><td>gold plated</td></tr> <tr><td>G</td><td>gold over silver</td></tr> <tr><td>K</td><td>gold / tin</td></tr> <tr><td colspan="2">Epoxy seal</td></tr> <tr><td>(none)</td><td>none seal</td></tr> <tr><td>E</td><td>epoxy seal</td></tr> <tr><td colspan="2">Bracket type</td></tr> <tr><td>(none)</td><td>std. Straight</td></tr> <tr><td>S</td><td>Snap-in type</td></tr> </table>	Q	silver plated	R	gold plated	G	gold over silver	K	gold / tin	Epoxy seal		(none)	none seal	E	epoxy seal	Bracket type		(none)	std. Straight	S	Snap-in type	<table border="1" style="width: 100%;"> <tr><td>(none)</td><td>9.40 (actuator S/V/X)</td></tr> <tr><td>T3</td><td>9.40 (actuator S/V/X)</td></tr> <tr><td colspan="2">Cap color</td></tr> <tr><td>1</td><td>white</td></tr> <tr><td>2</td><td>black</td></tr> <tr><td>3</td><td>red</td></tr> <tr><td>4</td><td>yellow</td></tr> <tr><td>5</td><td>blue</td></tr> <tr><td colspan="2">RoHS code</td></tr> <tr><td colspan="2">H = RoHS Compliant</td></tr> </table>	(none)	9.40 (actuator S/V/X)	T3	9.40 (actuator S/V/X)	Cap color		1	white	2	black	3	red	4	yellow	5	blue	RoHS code		H = RoHS Compliant	
TS-6																																																																																																																												
TS-6B																																																																																																																												
TS-6A																																																																																																																												
TS-6H																																																																																																																												
TS-6I																																																																																																																												
TS-7																																																																																																																												
TS-7B																																																																																																																												
TS-7A																																																																																																																												
TS-7H																																																																																																																												
TS-7I																																																																																																																												
TS-8																																																																																																																												
TS-8B																																																																																																																												
TS-8A																																																																																																																												
TS-8H																																																																																																																												
TS-8I																																																																																																																												
TS-9																																																																																																																												
TS-9B																																																																																																																												
TS-9A																																																																																																																												
TS-9H																																																																																																																												
TS-9I																																																																																																																												
TS-82																																																																																																																												
TS-82B																																																																																																																												
TS-82A																																																																																																																												
TS-82H																																																																																																																												
TS-82I																																																																																																																												
SP on-none-on																																																																																																																												
SP on-none-(on)																																																																																																																												
SP on-off-on																																																																																																																												
SP (on)-off-(on)																																																																																																																												
SP on-off-(on)																																																																																																																												
DP on-none-on																																																																																																																												
DP on-none-(on)																																																																																																																												
DP on-off-on																																																																																																																												
DP (on)-off-(on)																																																																																																																												
DP on-off-(on)																																																																																																																												
SP on-none-on																																																																																																																												
SP on-none-(on)																																																																																																																												
SP on-off-on																																																																																																																												
SP (on)-off-(on)																																																																																																																												
SP on-off-(on)																																																																																																																												
For Bushing E/E1/F/F1																																																																																																																												
S	9.40																																																																																																																											
T	5.33																																																																																																																											
U	7.37																																																																																																																											
For Bushing G/G1/J/J1																																																																																																																												
V	10.41																																																																																																																											
X	5.59																																																																																																																											
The 10-48 uns thread																																																																																																																												
E flat	5.59																																																																																																																											
F key-way	5.59																																																																																																																											
Non-thread																																																																																																																												
E1 (std.) flat	5.59																																																																																																																											
F1 key-way	5.59																																																																																																																											
1/4-40 uns thread																																																																																																																												
G flat	7.87																																																																																																																											
J key-way	6.60																																																																																																																											
Non-thread																																																																																																																												
G1 flat	7.87																																																																																																																											
J1 key-way	6.60																																																																																																																											
Q	silver plated																																																																																																																											
R	gold plated																																																																																																																											
G	gold over silver																																																																																																																											
K	gold / tin																																																																																																																											
Epoxy seal																																																																																																																												
(none)	none seal																																																																																																																											
E	epoxy seal																																																																																																																											
Bracket type																																																																																																																												
(none)	std. Straight																																																																																																																											
S	Snap-in type																																																																																																																											
(none)	9.40 (actuator S/V/X)																																																																																																																											
T3	9.40 (actuator S/V/X)																																																																																																																											
Cap color																																																																																																																												
1	white																																																																																																																											
2	black																																																																																																																											
3	red																																																																																																																											
4	yellow																																																																																																																											
5	blue																																																																																																																											
RoHS code																																																																																																																												
H = RoHS Compliant																																																																																																																												